

Infrared Data Association

IrDA Telecom Extensions to the IMC vCard Format



Version 1.0

October 15, 1997

Ericsson
Matsushita/Panasonic
Motorola
NEC
Nokia Mobile Phones, Ltd.
NTT DoCoMo
Puma
TU-KA Phone Kansai Inc.

Authors:

Petri Nykänen, Petri.Nykanen@nmp.nokia.com (IrDA Telecom SIG Chair, Nokia Mobile Phones, Ltd.)

Robert K. Lockhart (Motorola)

Contributors:

H. Chad Johnson (Ericsson),

Sheila Rader (Motorola),

Heli Helanummi (Nokia Mobile Phones, Ltd.)

Kazuya Anzawa (NTT DoCoMo),

Document Status: Version 1.0

INFRARED DATA ASSOCIATION (IrDA) - NOTICE TO THE TRADE -**SUMMARY:**

Following is the notice of conditions and understandings upon which this document is made available to members and non-members of the Infrared Data Association.

- Availability of Publications, Updates and Notices
- Full Copyright Claims Must be Honored
- Controlled Distribution Privileges for IrDA Members Only
- Trademarks of IrDA - Prohibitions and Authorized Use
- No Representation of Third Party Rights
- Limitation of Liability
- Disclaimer of Warranty
- Certification of Products Requires Specific Authorization from IrDA after Product Testing for IrDA Specification Conformance

IrDA PUBLICATIONS and UPDATES:

IrDA publications, including notifications, updates, and revisions, are accessed electronically by IrDA members in good standing during the course of each year as a benefit of annual IrDA membership. Electronic copies are available to the public on the IrDA web site located at irda.org. IrDA publications are available to non-IrDA members for a pre-paid fee. Requests for publications, membership applications or more information should be addressed to: Infrared Data Association, P.O. Box 3883, Walnut Creek, California, U.S.A. 94598; or e-mail address: info@irda.org; or by calling John LaRoche at (510) 943-6546 or faxing requests to (510) 934-5600.

COPYRIGHT:

1. Prohibitions: IrDA claims copyright in all IrDA publications. Any unauthorized reproduction, distribution, display or modification, in whole or in part, is strictly prohibited.
2. Authorized Use: Any authorized use of IrDA publications (in whole or in part) is under NONEXCLUSIVE USE LICENSE ONLY. No rights to sublicense, assign or transfer the license are granted and any attempt to do so is void.

DISTRIBUTION PRIVILEGES for IrDA MEMBERS ONLY:

IrDA Members Limited Reproduction and Distribution Privilege: A limited privilege of reproduction and distribution of IrDA copyrighted publications is granted to IrDA members in good standing and for sole purpose of reasonable reproduction and distribution to non-IrDA members who are engaged by contract with an IrDA member for the development of IrDA certified products. Reproduction and distribution by the non-IrDA member is strictly prohibited.

TRANSACTION NOTICE to IrDA MEMBERS ONLY:

Each and every copy made for distribution under the limited reproduction and distribution privilege shall be conspicuously marked with the name of the IrDA member and the name of the receiving party. Upon reproduction for distribution, the distributing IrDA member shall promptly notify IrDA (in writing or by e-mail) of the identity of the receiving party.

A failure to comply with the notification requirement to IrDA shall render the reproduction and distribution unauthorized and IrDA may take appropriate action to enforce its copyright, including but not limited to, the termination of the limited reproduction and distribution privilege and IrDA membership of the non-complying member.

TRADEMARKS:

1. Prohibitions: IrDA claims exclusive rights in its trade names, trademarks, service marks, collective membership marks and certification marks (hereinafter collectively "trademarks"), including but not limited to the following trademarks: INFRARED DATA ASSOCIATION (wordmark alone and with IR logo), IrDA (acronym mark alone and with IR logo), IR logo, IR DATA CERTIFIED (composite mark), and MEMBER IrDA (wordmark alone and with IR logo). Any unauthorized use of IrDA trademarks is strictly prohibited.
2. Authorized Use: Any authorized use of a IrDA collective membership mark or certification mark is by NONEXCLUSIVE USE LICENSE ONLY. No rights to sublicense, assign or transfer the license are granted and any attempt to do so is void.
3. Third party brands, trademarks, registered trademarks, service marks, and names are the property of their respective owners.

NO REPRESENTATION of THIRD PARTY RIGHTS:

IrDA makes no representation or warranty whatsoever with regard to IrDA member or third party ownership, licensing or infringement/non-infringement of intellectual property rights. Each recipient of IrDA publications, whether or not an IrDA member, should seek the independent advice of legal counsel with regard to any possible violation of third party rights arising out of the use, attempted use, reproduction, distribution or public display of IrDA publications.

IrDA assumes no obligation or responsibility whatsoever to advise its members or non-members who receive or are about to receive IrDA publications of the chance of infringement or violation of any right of an IrDA member or third party arising out of the use, attempted use, reproduction, distribution or display of IrDA publications.

LIMITATION of LIABILITY:

BY ANY ACTUAL OR ATTEMPTED USE, REPRODUCTION, DISTRIBUTION OR PUBLIC DISPLAY OF ANY IrDA PUBLICATION, ANY PARTICIPANT IN SUCH REAL OR ATTEMPTED ACTS, WHETHER OR NOT A MEMBER OF IrDA, AGREES TO ASSUME ANY AND ALL RISK ASSOCIATED WITH SUCH ACTS, INCLUDING BUT NOT LIMITED TO LOST PROFITS, LOST SAVINGS, OR OTHER CONSEQUENTIAL, SPECIAL, INCIDENTAL OR PUNITIVE DAMAGES. IrDA SHALL HAVE NO LIABILITY WHATSOEVER FOR SUCH ACTS NOR FOR THE CONTENT, ACCURACY OR LEVEL OF ISSUE OF AN IrDA PUBLICATION.

DISCLAIMER of WARRANTY:

All IrDA publications are provided "AS IS" and without warranty of any kind. IrDA (and each of its members, wholly and collectively, hereinafter "IrDA") EXPRESSLY DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE AND WARRANTY OF NON-INFRINGEMENT OF INTELLECTUAL PROPERTY RIGHTS.

IrDA DOES NOT WARRANT THAT ITS PUBLICATIONS WILL MEET YOUR REQUIREMENTS OR THAT ANY USE OF A PUBLICATION WILL BE UN-INTERRUPTED OR ERROR FREE, OR THAT DEFECTS WILL BE CORRECTED. FURTHERMORE, IrDA DOES NOT WARRANT OR MAKE ANY REPRESENTATIONS REGARDING USE OR THE RESULTS OR THE USE OF IrDA PUBLICATIONS IN TERMS OF THEIR CORRECTNESS, ACCURACY, RELIABILITY, OR OTHERWISE. NO ORAL OR WRITTEN PUBLICATION OR ADVICE OF A REPRESENTATIVE (OR MEMBER) OF IrDA SHALL CREATE A WARRANTY OR IN ANY WAY INCREASE THE SCOPE OF THIS WARRANTY.

LIMITED MEDIA WARRANTY:

IrDA warrants ONLY the media upon which any publication is recorded to be free from defects in materials and workmanship under normal use for a period of ninety (90) days from the date of distribution as evidenced by the distribution records of IrDA. IrDA's entire liability and recipient's exclusive remedy will be replacement of the media not meeting this limited warranty and which is returned to IrDA. IrDA shall have no responsibility to replace media damaged by accident, abuse or misapplication. ANY IMPLIED WARRANTIES ON THE MEDIA, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ARE LIMITED IN DURATION TO NINETY (90) DAYS FROM THE DATE OF DELIVERY. THIS WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS, AND YOU MAY ALSO HAVE OTHER RIGHTS WHICH VARY FROM PLACE TO PLACE.

CERTIFICATION and GENERAL:

Membership in IrDA or use of IrDA publications does NOT constitute IrDA compliance. It is the sole responsibility of each manufacturer, whether or not an IrDA member, to obtain product compliance in accordance with IrDA rules for compliance. All rights, prohibitions of right, agreements and terms and conditions regarding use of IrDA publications and IrDA rules for compliance of products are governed by the laws and regulations of the United States. However, each manufacturer is solely responsible for compliance with the import/export laws of the countries in which they conduct business. The information contained in this document is provided as is and is subject to change without notice.

CONTENTS:

1. INTRODUCTION	1
1.1 Purpose	1
1.2 Scope	1
1.3 References	1
2. BUSINESS CARD ADDITIONS	2
2.1 Wireless Phone and Paging System Types	2
2.1.1 Analog Cellular Telephones	2
2.1.2 Digital Cellular Telephones	2
2.1.3 Analog Cordless	3
2.1.4 Digital Cordless	3
2.1.5 Paging	3
2.2 Data Service Types	3
2.2.1 Access Rates	3
2.2.2 Data Formats	4
2.2.3 Supported Modem V-series Specifications	4
2.2.4 Access Structure	5
2.3 Messaging Service Types	5
2.3.1 Message Entry Protocols	5
2.3.2 Message Entry or System Type Protocol Revision Level	5
2.4 Service Center Definition	6
2.5 Device ID Definition	6
2.6 Wireless Electronic Mail Types	6
2.6.1 One and Two Way Paging Types, Protocols, and Revision Information	6
2.7 Explanatory Property Extension	7
2.7.1 Version	7
2.8 Informative Telephone Type Examples	7
2.9 Formal Definition	8

1. INTRODUCTION

1.1 PURPOSE

The purpose of this document is to propose a set of extensions to the IMC vCard Electronic Business Card vCard Version 2.1 specification [VCARD] for the wireless telephony industry. The extensions will lead to a wider acceptance of the vCard specification, as they open new areas in which the [VCARD] specification can be utilized. These extensions to the vCard specifically concentrate on further defining the properties related to telephone and data services. These extensions will enable automatic selection of the most suitable service.

1.2 SCOPE

The scope of the proposal is limited to proposing the addition of optional telephone system type, data service type, and messaging service type property parameters to the definition of the telephone number property and to proposing the addition of optional electronic mail type property parameters to the definition of the electronic mail property in [VCARD], section 2.4 Telecommunications Addressing Properties and to proposing the addition of optional explanatory properties to the definition of explanatory properties in [VCARD], section 2.6 Explanatory Properties.

1.3 REFERENCES

[VCARD] "vCard - The Electronic Business Card Exchange Format - Version 2.1", The Internet Mail Consortium (IMC), September 18, 1996, <http://www.imc.org/pdi/vcard-21.doc>.

2. BUSINESS CARD ADDITIONS

2.1 WIRELESS PHONE AND PAGING SYSTEM TYPES

The [VCARD] specification lists the Telephone types that can be used as identifiers for telephone numbers in section 2.4.1.1. To enable automatic selection of a wireless phone or paging system type, the following property parameter values are proposed to be included in the list of types.

It is important for devices that utilize the wireless systems to know which systems are available for communication; the data and messaging services in the systems are different from system to system, and it is impossible to do information exchange automatically without exact knowledge on the system available.

	Property Parameter
2.1.1 Analog Cellular Telephones	
<i>AMPS</i> : Advanced Mobile Phone System	AMPS
<i>NAMPS</i> : Narrowband Advanced Mobile Phone System	NAMPS
<i>NMT</i> : Nordic Mobile Telephone	
<i>NMT450</i>	NMT450
<i>NMT900</i>	NMT900
<i>TACS</i> : Total Access Communication System	TACS
ETACS	
NTACS	
<i>JTACS</i> : Japanese TACS system	JTACS
<i>J-ANALOG</i> : Japanese analog system (NTT)	J-ANALOG
A valid fallback for recipients that do not support these analog cellular telephone parameter types is to map such a telephone property into a telephone property value with the property parameter of "CELL".	
2.1.2 Digital Cellular Telephones	
<i>CDMA</i> : Code-Division Multiple Access; North American Digital Cellular	CDMA
<i>DCS1800</i> : GSM variant (on 1800 MHz)	DCS1800
<i>GSM</i> : Global System for Mobile Communications (GSM, on 900 MHz)	GSM
<i>GSM1900</i> : GSM variant (on 1900 MHz),	GSM1900
<i>IRIDIUM</i> : Satellite Phone System	IRIDIUM
<i>PDC</i> : Personal Digital Cellular	PDC
<i>TDMA</i> : Time-Division Multiple Access; North American Digital Cellular	TDMA
<i>WCDMA</i> : Wide-Band CDMA; Japanese Digital Cellular	WCDMA
<i>iDEN</i> Integrated Digital Enhanced Network	IDEN

A valid fallback for recipients that do not support these digital cellular telephone parameter types is to map such a telephone property into a telephone property value with the property parameter of "CELL".

2.1.3 Analog Cordless

<i>CT0</i> : Cordless Telephone 0	CT0
<i>CT1</i> : Cordless Telephone 1	CT1
<i>JCT</i> : Japanese Cordless Telephone	JCT
<i>PPS</i> : Personal Phone Series	PPS

A valid fallback for recipients that do not support these analog cordless telephone parameter types is to map such a telephone property into a nominal telephone property value without these property parameters.

2.1.4 Digital Cordless

<i>CT2</i> : Cordless Telephone 2	CT2
<i>DECT</i> : Digital European Cordless Telephone	DECT
<i>PHS</i> : Personal Handy Phone System	PHS

A valid fallback for recipients that do not support these digital cordless telephone parameter types is to map such a telephone property into a nominal telephone property value without these property parameters.

2.1.5 Paging

<i>One Way</i> : Paging	1WAY
<i>Two Way</i> : Two-Way Paging	2WAY

A valid fallback for recipients that do not support these paging telephone parameter types is to map such a telephone property into a telephone property value with the property parameter "PAGER".

2.2 DATA SERVICE TYPES

To enable automatic selection of data service types, the following property parameter values are proposed to be included in section 2.4.1.1 of [VCARD].

2.2.1 Access Rates

The data number in a versit business card may contain none, only the highest access rate, subset of the supported data rates, or all supported data rates. The supported access rate is proposed to be indicated in the following way:

Access Rate **DRATE=** <rate>[,<rate>[,...]]

where rate is indicated in kbit/second with format a[.b]; where 'a' represents integer part, and 'b' represents decimal part of the access rate in kbit/second. Extended format a[.b]/c[.d] is used when downlink (a.b), and uplink (c.d) access rates differ from each other.

The following list gives the typical rates that can be expected. Other rates may also be indicated, as long as the given format is used.

	Rate
0.3 kbit/sec	0.3
1.2 kbit/sec	1.2
1.2/0.075 kbit/sec	1.2/0.075
2.4 kbit/sec	2.4
4.8 kbit/sec	4.8

7.2 kbit/sec	7.2
9.6 kbit/sec	9.6
12 kbit/sec	12
14.4 kbit/sec	14.4
19.2 kbit/sec	19.2
24 kbit/sec	24
28.8 kbit/sec	28.8
38.4 kbit/sec	38.4
48 kbit/sec	48
56 kbit/sec	56
64 kbit/sec	64

A valid fallback for recipients that do not support these access rate telephone parameter types is to map such a telephone property into a nominal telephone property value without these property parameters.

2.2.2 Data Formats

The supported data format is proposed to be indicated in the following way:

Data Format **DFORM=** <d><p><s>

where <d> is the number of data bits, <p> the parity, and <s> is the number of stop bits

data bits	= 5, 6, 7, or 8	; Number of data bits in serial representation
parity	= O, E, N, M, or S	; Odd, even, none, mark, or space parity
stop bits	= 0, 1, 1.5, or 2	; Number of stop bits in serial representation

A valid fallback for recipients that do not support these data format telephone parameter types is to map such a telephone property into a nominal telephone property value without these property parameters.

2.2.3 Supported Modem V-series Specifications

CCITT V.21	V21
CCITT V.22	V22
CCITT V.22bis	V22bis
CCITT V.26ter	V26ter
CCITT V.32	V32
CCITT V.32bis	V32bis
CCITT V.34	V34
CCITT V.110	V110

A valid fallback for recipients that do not support these MODEM V-series telephone parameter types is to map such a telephone property into a telephone property value with the property parameter "MODEM".

2.2.4 Access Structure

Asynchronous modem	ASYNC
Synchronous modem	SYNC
PAD access	PAD
Packet access	PACKET

A valid fallback for recipients that do not support these access structure telephone parameter types is to map such a telephone property into a telephone property value with the property parameter "MODEM".

2.3 MESSAGING SERVICE TYPES

To enable automatic selection of messaging service types, the following property parameter values are proposed to be included in section 2.4.1.1 of [VCARD].

2.3.1 Message Entry Protocols

Short Message Service	SMS
Pager Alphanumeric Message Entry	TAP
Pager Advanced Message Entry	TDP

The protocols to be used with these dial-up access methods are defined by the respective protocol maintenance organizations (e.g., TAP (Telocator Alphanumeric Protocol) and TDP (Telocator Data Paging Suite of Protocols) are defined by the Personal Communications Industry Association) as defined in the section on Reference Information.

A valid fallback for recipients that do not support these telephone parameter types is to map such an email property into a nominal telephone property value without any email address type property parameter.

2.3.2 Message Entry or System Type Protocol Revision Level

This property parameter specifies the revision level of the message entry protocol or cellular or paging system type. The revision level is proposed to be indicated in the following way:

Revision Level WREV=<wrev>

where wrev is indicated as a number with format a[.b]; where 'a' represents integer part, and 'b' represents decimal part of wrev.

Examples of this property as used with a pager using TAP for alphanumeric entry follow:

```
TEL;PAGER;1WAY;TAP;PIN=987-6543;MODEM;DRATE=2.4;ASYNC;DFORM=7E1:+1 (555) 323-3223
```

```
TEL;PAGER;TAP;WREV=1.8;PIN=(555) 987-6543:+1 (555) 323-3223
```

A valid fallback for recipients that do not support these message entry or system type protocol revision level telephone parameter types is to map such a telephone property into a nominal telephone property value without these property parameters.

2.4 SERVICE CENTER DEFINITION

To enable automatic two-stage dialing¹, the following property parameter value is proposed to be included in section 2.4.1.1 of [VCARD].

Service Center **SC=** <phone nbr>

where <phone nbr> is as defined in 2.4.1 of [VCARD].

A valid fallback for recipients that do not support these service center telephone parameter types is to map such a telephone property into a nominal telephone property value without this property parameter.

2.5 DEVICE ID DEFINITION

To enable page entry dialing² in paging systems requiring both a paging system access number (SC) and a pager identification number (PIN) instead of the single PAGER access number, the following property parameter value is proposed to be included in section 2.4.1.1 of [VCARD].

Personal Identification Number **PIN=**<phone nbr>

where <phone nbr> is as defined in 2.4.1 of [VCARD].

A valid fallback for recipients that do not support these device identifier telephone parameter types is to map such a telephone property into a nominal telephone property value without this property parameter.

2.6 WIRELESS ELECTRONIC MAIL TYPES

The [VCARD] specification lists the Electronic Mail types that can be used as identifiers for electronic mail access methods in section 2.4.2.1. To enable automatic selection of wireless electronic mail types, the following property parameter values are proposed to be included in the list of types.

2.6.1 One and Two Way Paging Types, Protocols, and Revision Information

To enable automatic alphanumeric and data message entry to paging systems through email-like Internet access methods (e.g., name@domain or URL), the following paging protocol property parameter values are proposed to be included in section 2.4.2.1 of [VCARD]

<i>SMS:</i>	Short Message Service	SMS
<i>TAP:</i>	Telocator Alphanumeric Protocol	TAP
<i>TDP:</i>	Telocator Data Paging Suite	TDP
<i>One Way:</i>	Paging	1WAY
<i>Two Way</i>	Two-Way Paging	2WAY
Revision Level		WREV
Personal Identification Number		PIN

¹ Two-stage dialing procedure is one of three procedures proposed for access to CDMA data services. In this procedure it is required that a Mobile Terminating data call is made by first dialing a service center number, and then dialing the cellular number of the subscriber. The phone number of the service center identifies the intended data service type, and the phone number of the subscriber identifies the intended handset.

² Two-stage dialing procedure is required when sending a message to a paging device in a paging system with a common access number for all paging devices. The paging access call is made by first dialing a service center number, and then dialing the personal identification number of the subscriber device.

where these property parameter values are as defined in [VCARD] section 2.4.1.1.

Carrier Address

CARRIER

where the Carrier Address is an address in the form of a specific addressing type.

Examples of these properties as used with ReFLEX(tm) two-way pagers using TDP for message entry follow:

```
EMAIL;TDP;CARRIER=carrier.net;John.Public
```

```
EMAIL;TDP;WREV=3.0;2WAY:110-1245@carrier.net
```

A valid fallback for recipients that do not support these wireless email parameter types is to map such an email property into a nominal email property value without these property parameters.

2.7 EXPLANATORY PROPERTY EXTENSION

2.7.1 Version

The vCard datastreams containing these extensions need to be clearly identified. Therefore, any implementations conforming to these specifications must specify the VERSION property with a value of "2.1-IrDA". For example:

```
VERSION:2.1-IrDA
```

A valid fallback for recipients that do not support this version of the vCard is to assume the nominal vCard version 2.1 datastream and process all extensions associated with this proposal as proposed in the above sections.

2.8 INFORMATIVE TELEPHONE TYPE EXAMPLES

The vCard formats for wireless device numbers are defined in [VCARD] as follows:

```
TEL;CELL:+1 (555) 123-4567 and
```

```
TEL;PAGER:+1 (555) 765-4321
```

which does not enable indication of the type of the cellular system or pager access method. To be able to indicate which cellular or paging system is associated with a phone number, a note could be grouped with a phone number declaration.

```
A.TEL;CELL:+1 (555) 123-4567
```

```
A.NOTE:This is my AMPS (analog) phone
```

```
B.TEL;CELL:+1 (555) 345-6789
```

```
B.NOTE:This is my TDMA (digital) phone
```

```
C.TEL;PAGER:+1 (555) 987-6543
```

```
C.NOTE:This is my FLEX(tm) (roaming) pager
```

However, the contents of the note are not structured and this makes it difficult to parse the note to check if it contains information on the cellular or paging system type. To enable automatic identification of the phone numbers and the services associated with them, this section of this paper defines additions that can be utilized the following way:

To indicate an AMPS cellular phone number:

```
TEL;CELL;AMPS:+1 (555) 123-4567
```

To indicate a TDMA cellular phone number:

```
TEL;CELL;TDMA:+1 (555) 345-6789
```

To indicate a numeric message paging phone number with PIN:

```
TEL;PAGER;PIN=(555) 987-6543:+1 (555) 234-5678
```

To indicate a TAP-based alphanumeric message paging phone number with PIN (555) 987-6543 and with access rate 2400 BPS, asynchronous, data format 7E1:

```
TEL;PAGER;TAP;PIN=(555) 987-6543;MODEM;DRATE=2.4;ASYNC;DFORM=7E1:+1
(555) 323-3223
```

To indicate a GSM1900 Short Message Service phone number:

```
TEL;CELL;GSM1900;MSG;SMS:+1 (555) 234-5678
```

To indicate a GSM1900 modem number with access rate 9600 BPS, asynchronous, data format 7E1:

```
TEL;CELL;GSM1900;MODEM;DRATE=9.6;ASYNC;DFORM=7E1:+1 (555) 456-7890
```

To indicate a CDMA modem number with access rate 9600 BPS, accessed using two-stage dialing:

```
TEL;CELL;CDMA;MODEM;DRATE=9.6;SC=+1(555)123-4321:+1(555)123-6789
```

2.9 FORMAL DEFINITION

The following extensions to the formal definition in section 3.9 of [VCARD] are proposed to be added:

```
proposed_param = param
/ "DRATE" [ws] "=" [ws] drateval
/ "DFORM" [ws] "=" [ws] dformval
/ "SC" [ws] "=" [ws] 7bit
/ "PIN" [ws] "=" [ws] 7bit
/ "WREV" [ws] "=" [ws] wrevval

proposed_knowntype = knowntype
/ "AMPS" / "NAMPS" / "TACS" / "JTACS" / "J-ANALOG"
/ "NMT450" / "NMT900"
/ "TDMA" / "CDMA" / "WCDMA" / "GSM" / "DCS1800" / "GSM1900"
/ "IRIDIUM" / "PDC" / "IDEN"
/ "CT0" / "CT1" / "JCT" / "PPS" / "CT2" / "DECT" / "PHS"
/ "1WAY" / "2WAY"
/ "V21" / "V22" / "V22bis" / "V26ter" / "V32" / "V32bis" / "V34" / "V110"
/ "ASYNC" / "SYNC" / "PAD" / "PACKET"
/ "SMS" / "TAP" / "TDP" / "CARRIER"

bitparts = "5" / "6" / "7" / "8"

parityparts = "O" / "E" / "N" / "M" / "S"
```

stopparts = “0” / “1” / “1.5” / “2”
dformval = bitparts parityparts stopparts
drateval = “0.3” / “1.2” / “1.2/0.075” / “2.4” / “4.8” / “7.2” / “9.6”
/ “12” / “14.4” / “19.2” / “24” / “28.8” / “38.4” / “48”
/ “56” / “64”
/ *(7bit “.”) 7bit
/ (*(7bit “.”) 7bit “/” *(7bit “.”) 7bit)
/ drateval “,” drateval
wrevval = *(7bit “.”) 7bit