

JsSpec Cheat Sheet

Basic form:

```
describe('what we're testing', {  
  'test title/specific behavior to test': function(){  
    //test here...  
    value_of(something producing a value).test(testing against);  
  }, more tests....  
})
```

Can also have:

before_each or after_each - equivalent to setup and tear down methods in most other testing frameworks.

Tests:

should_be	should_not_be	(what to check against)
should_be_empty	should_not_be_empty	()
should_be_true	should_not_be_true	()
should_be_false	should_not_be_false	()
should_include	should_not_include	(array item, object key)
should_be_null	should_not_be_null	()
should_be_undefined	should_not_be_undefined	()
should_match	should_not_match	(regular expression)
should_fail("todo")		

length checks:

should_have	(x, [characters items some property])
should_have_exactly	
should_have_at_least	
should_have_at_most	

Conditionals:

These can be combined with || or &&
'test title [[JSSpec.Browser....]]':

Following is a full list of predefined constants:

JSSpec.Browser.Trident	JSSpec.Browser.Webkit	JSSpec.Browser.Gecko
JSSpec.Browser.Presto	JSSpec.Browser.Mac	JSSpec.Browser.Ubuntu
JSSpec.Browser.Win	JSSpec.Browser.IE	JSSpec.Browser.IE6
JSSpec.Browser.IE7	JSSpec.Browser.IE8	JSSpec.Browser.FF
JSSpec.Browser.FF2	JSSpec.Browser.FF3	JSSpec.Browser.Safari